



USER HANDBOOK

STERLING

SUB-MACHINE GUN

9-mm. MK 4

(S.M.G. 9mm. L.2.A.3.)

STERLING ARMAMENT COMPANY LIMITED

DAGENHAM . ESSEX . ENGLAND

CONTRACTORS TO MINISTRY OF DEFENCE, HER MAJESTY'S GOVERNMENT,
CROWN AGENTS, AND OVERSEAS GOVERNMENTS.
(War Department Approved Inspection Organisation)

Telephone: 01-595 2226

Cables: STERLING, DAGENHAM, ENGLAND

STERLING SUB-MACHINE GUN 9-mm. MK. 4.



Above: Shown with butt extended and bayonet fitted
Below: Shown folded

CONTENTS

SECTION 1—GENERAL

	page	para.
Introduction	4	1.0
Technical Details	4	2.0
Special Features	6	3.0
Butt	6	3.1
Body	6	3.2
Trigger and Safety Mechanism	6	3.3
Backsight	6	3.4
Bayonet	6	3.5

SECTION 2—DESCRIPTION AND OPERATION

The Backward Action	8	4.1
The Forward Action	9	4.2
Action of the Trigger Mechanism	10	5.0
Single Shot Fire	10	5.1
Automatic Fire	13	5.2
Applied Safety	13	5.3
To Open Butt	14	6.0
To Close Butt	14	7.0

SECTION 3—STRIPPING AND ASSEMBLY

	page	para.
Elementary Stripping and Assembly	15	8.0
To Remove Return Spring	15	8.1
To Remove Trigger Group Assembly	16	8.2
Advanced Stripping and Assembly	17	9.0
To Remove Ejector	17	9.1
To Strip Trigger Group	18	9.2
To Remove Extractor	19	9.3
To Remove Pistol Grip	19	9.4
To Remove Barrel	20	9.5
To Strip Magazine	20	9.6
To Remove Foresight	21	9.7
To Remove Backsight	21	9.8
To Assemble Trigger Group	21	9.9
To Replace Barrel	21	9.10
To Assemble Foresight	21	9.11
To Assemble Backsight	22	9.12
To Assemble Magazine	22	9.13

SECTION 4—ZEROING

SECTION 5—CLEANING

SECTION I—GENERAL

1.0 INTRODUCTION. The Sterling Sub-Machine Gun, Mark 4, is a light and easily handled weapon which will selectively fire automatically or single shot. Standard 9 mm Parabellum ammunition is used.

It is a short range weapon normally used for engagement at ranges up to 200 yards. It may be used at longer ranges dependant on the skill of the firer.

On account of its accuracy, lightness and reliability, the gun can be regarded as a general purpose weapon.

It is automatic, being operated by case reaction or "blow back" whether fired "single shot" or in bursts.

2.0 TECHNICAL DETAILS

Calibre	9 mm	9 mm
Length—butt folded	19 inches	48.2 cms
—butt extended	27 inches	69 cms
Weight—machine gun only	6 lbs (approx.)	2.7 Kg (approx.)
—with full magazine (34 rds)	7 lb 10 oz (approx.)	3.5 Kg (approx.)
—with full magazine and bayonet ..	8 lb 4 oz (approx.)	3.73 Kg (approx.)
Barrel —length	7.8 inches	19.8 cms
—number of grooves	6	
—pitch of rifling	1 turn in 9.84 inches ..	25 cms
—twist of rifling	Right hand	
Sights —radius	16.1 inches	41 cms
—type	Rear—aperture	
	Fore—blade	
—range settings	100 and 200 yards	100 and 200 metres
Cyclic rate of fire	550 r.p.m. approx.	

TERMINAL VELOCITY AND KINETIC ENERGY OF STANDARD 9 mm BULLET

RANGE		VELOCITY		KINETIC ENERGY	
Yards	Metres	Ft/Sec	M/Sec	Ft/lbs	Kgm
0	0	1280	390	447	62.2
109	100	1115	340	339	47.0
218	200	975	298	262	36.4
327	300	872	266	207	28.7
436	400	780	238	167	23.2
545	500	700	214	135	18.8
654	600	632	193	109	15.2
763	700	572	174	89	12.3
872	800	518	158	74	10.2

